

MATERIAL SAFETY DATA SHEET

Page 1(4)

SATSUMA SUP 854  
Date: 20 August 2004  
MSDS Revision: 01

1. Identification of the substance/preparation and company

Product name : SATSUMA SUP 854  
Company name : The Soap Kitchen  
Company address : 11a South Street  
Torrington  
Devon  
EX38 8AA  
Emergency phone : 01805 622944

2. Composition/information on ingredients

Chemical identification: Fragrance composition: multicomponent mixture of natural and

synthetic aromatic materials.

CAS number : Not applicable, product is a mixture.  
EINECS number : Not applicable, product is a mixture.

Contains Conc%	CAS/EINECS	Hazard Symbols
ALCOHOL C12 0.1-1	112-54-9	N; R 50
Aldehyde C10 / DECANAL 1-5	/203-982-0 112-31-2	Xi; R 38
Aldehyde C8 / OCTANAL 1-5	/203-957-4 124-13-0	Xi; R 10-36-38
Allyl Caproate FCC A0700-0 (ALLYL HEXAN 1-5	/204-683-8 123-68-2	Xn-N; R 21/22-51/53
Benzyl Alcohol 1-5	OATE) /204-642-4 100-51-6	Xn; R 20/22
(S) DELTA DAMASCONE (937856) 0.1-1	/202-859-9 57378-68-4	Xi; R 43
(L) ORANGE OIL >50	/260-709-8 8028-48-6	Xn; R 10-65
	/232-433-8	

3. Hazards identification

General : When undiluted and not properly handled, can be irritating to the skin and eyes and upon inhalation. Combustible material that can sustain a fire.  
Hazard symbol : Xn, Harmful.  
Risk phrases : R65, Harmful: May cause lung damage if swallowed.  
Environment : When spilled, can contaminate soil, ground and surface water.

MATERIAL SAFETY DATA SHEET

SATSUMA SUP 854  
Date: 20 August 2004  
MSDS Revision: 01

Page 2(4)

4. First-aid measures

- Inhalation : Remove from exposure site to fresh air, keep at rest, and obtain medical attention.
- Eye exposure : Flush immediately with water for at least 15 minutes. Contact physician if symptoms persist.
- Skin exposure : Remove contaminated clothes. Wash thoroughly with soap and water. Contact physician if irritation persists.
- Ingestion : Rinse mouth with water and obtain medical attention.
- Others : Take Risk and Safety phrases (section 15) into consideration.

5. Fire-fighting measures

- Extinguishing media : Carbon dioxide, dry chemical, foam.  
Do not use a direct water-jet on burning material.

6. Accidental release measures

- Personal precautions : Avoid inhalation and contact with skin and eyes. A self-contained breathing apparatus is recommended in case of a major spill.
- Spillage : Remove ignition sources. Provide adequate ventilation. Avoid excessive inhalation of vapours. Gross spillage should be contained immediately by use of sand or inert powder and disposed of according to local regulations.
- Environmental precautions : Keep away from drains, surface and ground water, and soil.

7. Handling and storage

- Handling : Apply according to good manufacturing and industrial hygiene practices with proper ventilation. Do not drink, eat or smoke while handling. Respect good personal hygiene.
- Storage : Store in a cool, dry and ventilated area away from heat sources and protected from light in tightly closed original containers. Avoid plastic and uncoated metal containers. Keep air contact to a minimum.

Fire protection : Keep away from ignition sources and naked flame.

MATERIAL SAFETY DATA SHEET

SATSUMA SUP 854  
Date: 20 August 2004  
MSDS Revision: 01

Page 3(4)

8.Exposure controls/personal protection

Respiratory protection : Avoid excessive inhalation of concentrated vapours.  
Eye protection : Wear safety glasses.  
Skin protection : Avoid skin contact. Use chemically resistant gloves as needed.

9.Physical and chemical properties

Appearance : Not determined.  
Odour : Not determined.  
Flash point : Not determined.  
Oxidising property : None expected.

10.Stability and reactivity

Reactivity : Presents no significant reactivity hazard, by itself or in contact with water. Avoid contact with strong acids, alkali or oxidising agents.  
Decomposition : Carbon monoxide and unidentified organic compounds may be formed during combustion.

11.Toxicological information

Based on the ingredients in this composition and their concentrations, this product is according to the conventional method of EEC directive 1999/45/EC classified as:  
Safe when used as directed.

12.Ecological information

General : This material is unlikely to accumulate in the environment and environmental problems under normal use conditions are unexpected.

13.Disposal considerations

-----  
Dispose of according to local regulations.  
Avoid disposing into drainage systems and into the environment.

#### 14. Transport information

-----

	Class	Pack group	Sub risk	UN no	IMDG page
Road (CDGRR)	: not restricted.				
Air (IATA)	: not restricted.				
Sea (IMDG)	: not restricted.				

#### MATERIAL SAFETY DATA SHEET

-----

SATSUMA SUP 854  
Date: 20 August 2004  
MSDS Revision: 01

Page 4(4)

#### 15. Regulatory information

-----

Classification Packaging / Labelling (Directive 1999/45/EC)  
Hazard symbol : Xn, Harmful.  
Contains ORANGE OIL.  
Contains DELTA DAMASCONE (937856). May produce an allergic reaction.  
Risk phrases : R65, Harmful: May cause lung damage if swallowed.  
Safety phrases : S62, If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

#### 16. Other information

-----

Conc % Limits (\*) : XnR65=11.48% IFRA=5.000%

Maximum usage limited by IFRA.

(\*) These are the maximum percent concentrations that this material can be used in a non-hazardous product without the indicated risk being applicable to that product.

The shelf life of this product is 12 months from date of manufacture.

The information in this leaflet is to the best of our knowledge true and accurate but all data, instructions, recommendations and/or suggestions are made without guarantee.

