

MATERIAL SAFETY DATA SHEET

Page 1(5)

OULD WOOD 28065
Date: 30 March 2011
MSDS Revision: 01

Date created: 07/01/10

1. Identification of the substance/preparation and company

Product name : OUD WOOD 28065
Company name : The Soap Kitchen
Company address : Unit 2e Hatchmoor Ind. Est
Hatchmoor Road
Torrington
Devon
EX38 7HP. UK
Emergency phone : +44 1805 622944
Fax : +44 870 4586724

2. Hazards identification

General : When undiluted and not properly handled, can be irritating to the skin and eyes and upon inhalation. Combustible material that can sustain a fire.
Hazard symbol : Xi, Irritant.
: N, Dangerous for the environment.
Risk phrases : R43, May cause sensitisation by skin contact.
: R51/53, Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Environment : When spilled, can contaminate soil, ground and surface water.

MATERIAL SAFETY DATA SHEET

OULD WOOD 28065
 Date: 30 March 2011
 MSDS Revision: 01

Page 2(5)

Date created: 07/01/10

3.Composition/information on ingredients

Chemical identification: Fragrance composition: multicomponent mixture of natural and synthetic aromatic materials.

CAS number : Not applicable, product is a mixture.

EINECS number : Not applicable, product is a mixture.

Contains	CAS/EINECS	Hazard Symbols	Conc%
(L) 3 and 4-(4-hydroxy-4-methylpentyl)-3-cyclohexene-1-carboxaldehyde	31906-04-4 /250-863-4	Xi; R 43	1-5
Alpha Pinene	80-56-8 /201-291-9	Xn-N; R 10-43-50/53-65	0.1-1
benzyl benzoate	120-51-4 /204-402-9	Xn; R 22	5-25
BETA IONONE	14901-07-6 /238-969-9	N; R 51/53	1-5
GALAXOLIDE 50 DEP	1222-05-5 /-	Xi; R 36/37/38	5-25
HEXYL SALICYLATE	6259-76-3 /228-408-6	Xi-N; R 38-50/53	1-5
ISO E SUPER	54464-57-2 /259-174-3	N; R 51/53	25-50
limonene	5989-27-5 /227-813-5	Xi-N; R 38-43-50/53	0.1-1
pinenes	80-56-8 /-	Xi-N; R 50/53-43	0.1-1
Tonalid	1506-02-1 /216-133-4	Xn-N; R 22-50/53	0.1-1

Contains allergens as defined under the European Cosmetics Directive

3 and 4-(4-hydroxy-4-methylpentyl)-3-cyclohexene-1-carboxaldehyde (2.4048%)

alpha iso methyl ionone (0.8400%)

benzyl benzoate (20.0006%)

citral (0.0244%)

citronellol (0.0001%)

coumarin (0.0005%)

eugenol (0.0002%)

geraniol (0.0083%)

hexyl cinnamic aldehyde (0.0006%)

limonene (0.6533%)

linalool (0.8304%)

(L) Ingredient must be disclosed on a label ("Contains _").

(S) Ingredient must be disclosed on a label as a sensitiser

("Contains _ . May cause an allergic reaction.").

MATERIAL SAFETY DATA SHEET

OLD WOOD 28065
Date: 30 March 2011
MSDS Revision: 01

Page 3(5)

Date created: 07/01/10

4. First-aid measures

Inhalation : Remove from exposure site to fresh air, keep at rest, and obtain medical attention.
Eye exposure : Flush immediately with water for at least 15 minutes. Contact physician if symptoms persist.
Skin exposure : Remove contaminated clothes. Wash thoroughly with soap and water. Contact physician if irritation persists.
Ingestion : Rinse mouth with water and obtain medical attention.
Others : Take Risk and Safety phrases (section 15) into consideration.

5. Fire-fighting measures

Extinguishing media : Carbon dioxide, dry chemical, foam.
Do not use a direct water-jet on burning material.

6. Accidental release measures

Personal precautions : Avoid inhalation and contact with skin and eyes. A self-contained breathing apparatus is recommended in case of a major spill.
Spillage : Remove ignition sources. Provide adequate ventilation. Avoid excessive inhalation of vapours. Gross spillage should be contained immediately by use of sand or inert powder and disposed of according to local regulations.
Environmental precautions : Keep away from drains, surface and ground water, and soil.

7. Handling and storage

Handling : Apply according to good manufacturing and industrial hygiene practices with proper ventilation. Do not drink, eat or smoke while handling. Respect good personal hygiene.
Storage : Store in a cool, dry and ventilated area away from heat sources and protected from light in tightly closed original containers. Avoid plastic and uncoated metal containers. Keep air contact to a minimum.
Fire protection : Keep away from ignition sources and naked flame.

8. Exposure controls/personal protection

Respiratory protection : Avoid excessive inhalation of concentrated vapours.
Eye protection : Wear safety glasses.
Skin protection : Avoid skin contact. Use chemically resistant gloves as needed.

MATERIAL SAFETY DATA SHEET

OULD WOOD 28065
Date: 30 March 2011
MSDS Revision: 01

Page 4(5)

Date created: 07/01/10

9. Physical and chemical properties

Appearance : Not determined.
Odour : Not determined.
Flash point : Not determined.
Oxidising property : None expected.

10. Stability and reactivity

Reactivity : Presents no significant reactivity hazard, by itself or in contact with water. Avoid contact with strong acids, alkali or oxidising agents.
Decomposition : Carbon monoxide and unidentified organic compounds may be formed during combustion.

11. Toxicological information

Based on the ingredients in this composition and their concentrations, this product is according to the conventional method of EEC directive 1999/45/EC classified as:
May cause sensitisation by skin contact.

12. Ecological information

General : This material is unlikely to accumulate in the environment and environmental problems under normal use conditions are unexpected.

13. Disposal considerations

Dispose of according to local regulations.
Avoid disposing into drainage systems and into the environment.

14. Transport information

Class Pack group Sub risk UN no IMDG page
Road (CDGRR) : not restricted.
Air (IATA) : not restricted.
Sea (IMDG) : not restricted.

15. Regulatory information

Classification Packaging / Labelling (Directive 1999/45/EC)
Hazard symbol : Xi, Irritant.
 : N, Dangerous for the environment.
Contains 3 and 4-(4-hydroxy-4-methylpentyl)-3-cyclohexene-1-carboxaldehyde.
Risk phrases : R43, May cause sensitisation by skin contact.
 : R51/53, Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Safety phrases : S24, Avoid contact with the skin.

MATERIAL SAFETY DATA SHEET

OULD WOOD 28065
Date: 30 March 2011
MSDS Revision: 01

Page 5(5)

Date created: 07/01/10

15.Regulatory information

Classification Packaging / Labelling (Directive 1999/45/EC)

- : S37, Wear suitable gloves.
- : S61, Avoid release to the environment. Refer to special instructions/safety data sheet.

16.Other information

Conc % Limits (*) : XiR43=41.58% NR51/53=45.14% R52/53=4.51% R53=79.46%
IFRA=100.000% IFRANS=100.000%

(*) These are the maximum percent concentrations that this material can be used in a non-hazardous product without the indicated risk being applicable to that product.

The shelf life of this product is 24 months from date of manufacture.

The information in this leaflet is to the best of our knowledge true and accurate but all data, instructions, recommendations and/or suggestions are made without guarantee.